NEO DUMPS

Salesforce

Javascript-Developer-I Exam

Javascript Developer I

Questions & Answers

(Demo Version - Limited Content)

Thank you for Downloading Javascript-Developer-I exam PDF Demo

Get Full File:

https://neodumps.com/javascript-developer-i-dumps/

WWW.NEODUMSP.COM

Question: 1

Refer to the code below:
01 const exec = (item, delay) =>{
02 new Promise(resolve => setTimeout(() => resolve(item), delay)),
03 async function runParallel() {
04 Const (result1, result2, result3) = await Promise.all{
05 [exec ('x', '100') , exec('y', 500), exec('z', '100')]
06);07 return `parallel is done: $(result1) $(result2)$(result3)`;
08 }}}
Which two statements correctly execute the runParallel () function?
Choose 2 answers

A. Async runParallel () .then(data);
B. runParallel ( ). done(function(data){
return data;});
C. runParallel () .then(data);
D. runParallel () .then(function(data)
return data

Answer: B, D

Explanation:

Question: 2

A developer needs to test this function:
01 const sum3 = (arr) => (
02 if (!arr.length) return 0,
03 if (arr.length === 1) return arr[0],
04 if (arr.length === 2) return arr[0] + arr[1],
05 return arr[0] + arr[1] + arr[2],
06);
Which two assert statements are valid tests for the function?
Choose 2 answers

A. console.assert(sum3(1, '2')) == 12);
B. console.assert(sum3(0)) == 0);
C. console.assert(sum3(-3, 2)) == -1);
D. console.assert(sum3('hello', 2, 3, 4)) === NaN);

Answer: A, C

Explanation:

Question: 3

Which statement phrases successfully?

A. JSON.parse (‘ foo ’);
B. JSON.parse (“ foo ”);
C. JSON.parse(“ ‘ foo ’ ”);
D. JSON.parse(‘ “ foo ” ’);

Answer: D

Explanation:

Question: 4

Refer to the code below:
01 let car1 = new promise((_, reject) =>
02 setTimeout(reject, 2000, “Car 1 crashed in”));
03 let car2 = new Promise(resolve => setTimeout(resolve, 1500, “Car 2 completed”));
04 let car3 = new Promise(resolve => setTimeout (resolve, 3000, “Car 3 Completed”));
05 Promise.race([car1, car2, car3])
06 .then(value => (
07 let result = $(value) the race. `;
08))
09 .catch(arr => (
10 console.log(“Race is cancelled.”, err);
11));
What is the value of result when Promise.race executes?

A. Car 3 completed the race.
B. Car 1 crashed in the race.
C. Car 2 completed the race.
D. Race is cancelled.

Answer: C

Explanation:

Question: 5

www.neodumps.com

Refer to the code below:

```
for(let number =2 ; number <= 5 ; number += 1 ) {
// insert code statement here
}
```

The developer needs to insert a code statement in the location shown. The code statement has these requirements:

1. Does require an import
2. Logs an error when the boolean statement evaluates to false
3. Works in both the browser and Node.js

Which meet the requirements?

A. assert (number % 2 === 0);
B. console.error(number % 2 === 0);
C. console.debug(number % 2 === 0);
D. console.assert(number % 2 === 0);

Answer: B

Thank You for trying Javascript-Developer-I PDF Demo

https://neodumps.com/javascript-developer-i-dumps/

Start Your Javascript-Developer-I Preparation

[Limited Time Offer] Use Coupon "SAVE20" for extra 20% discount on the purchase of PDF file. Test your Javascript-Developer-I preparation with actual exam questions